



Outdoor walk-over luminaire for ground surface installation
 Max. load pressure 500 kg
 Material: low copper content die-cast aluminium
 Diffuser: UV resistant opal polycarbonate
 Light source: mains voltage LED module, compatible with phase-cut dimmers
 Anticorrosional anodized aluminium cable gland with watertight internal resin coating - AQUASTOP system / Luminaire supplied with 1,5 m polyurethane buriable cable 3x1 H07RN-F
 Stainless steel screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):
MT7 7 m cable length

Dimensions	Ø 180 x H 43 mm
Light source	LED
Multiple sources	2x
Wattage	8 W
Power supply	220-240 V 50/60 Hz
Light source output	736 lm
System output	188 lm
System efficiency	24 lm/W
Color Rendering Index – CRI	80
LED energy class	F
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	1.13 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE

on request:

CO CORTEN
BR BRONZE

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

SQUEEZE

THE SERIES

