

Outdoor wall steplight luminaire with minimum thickness for surface installation

Material: low copper content die-cast aluminium

Diffuser: UV resistant polycarbonate

Light source: mains voltage LED module, compatible with phase-cut dimmers

Rear single cable entry / Spacer optional accessory for side cable entry

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

24V 24V low voltage

Dimensions	120 x 120 x 26 mm
Light source	LED
Multiple sources	4x
Wattage	8 W
Power supply	220-240 V 50/60 Hz
Light source output	764 lm
System output	500 lm
System efficiency	63 lm/W
Color Rendering Index – CRI	80
LED energy class	F
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	0.43 kg
Conformity	CE UK CA

CODE OPTIONS



FINISH

- AG** ALUMINIUM GREY
- AN** ANTHRACITE
- CO** CORTEN
- BR** BRONZE
- BI** WHITE

COLOUR TEMP.

- 27K** 2700K
- 3K** 3000K
- 4K** 4000K

ACCESSORIES



STAMP THE SERIES

