

Outdoor wall steplight luminaire with minimum thickness for surface installation

Material: low copper content die-cast aluminium

Diffuser: UV resistant polycarbonate

Light source: mains voltage LED module, compatible with phase-cut dimmers

Rear single cable entry / Spacer optional accessory for side cable entry

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

**24V** 24V low voltage

Dimensions	<b>120 x 120 x 26 mm</b>
Light source	<b>LED</b>
Multiple sources	<b>4x</b>
Wattage	<b>8 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>764 lm</b>
System output	<b>500 lm</b>
System efficiency	<b>63 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>F</b>
LED lifetime	<b>L70 B50 &gt; 50.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class I</b>
IP rating	<b>IP 65</b>
Impact resistance rating	<b>IK 10 (20 joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>0.43 kg</b>
Conformity	<b>CE UK CA</b>

**CODE OPTIONS**



**FINISH**

- AG** ALUMINIUM GREY
- AN** ANTHRACITE
- CO** CORTEN
- BR** BRONZE
- BI** WHITE

**COLOUR TEMP.**

- 27K** 2700K
- 3K** 3000K
- 4K** 4000K

ACCESSORIES



**STAMP** THE SERIES

