









Pole complete with luminaire  
 Material: aluminium  
 Diffuser: ultra-white opal tempered glass  
 External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately  
 Light source: LED unit  
 Supplied with H05RN-F pre-wired cable (optional waterproof connections to be ordered separately - codes 1941-1944)  
 Finish with double painting after anti-corrosion treatments: epoxy-based primer and polyester powder coating

Dimensions	128 x 44 x H 300 mm
Light Source	LED
Power	6 W
Voltage/Frequency	24V DC
Light output source	698 lm
LUMEN OUTPUT	302 lm
System efficiency	50 lm/W
Color Rendering Index – CRI	80
LED energy class	F
Electrical insulation class	Class III
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	1.8 kg
Certifications	CE UK CA

**CODE OPTIONS**

FINISH	COLOUR TEMP.	OPTIC
<b>AG</b> ALUMINIUM GREY	<b>3K</b> 3000K	<b>standard</b> DIFFUSE
<b>AN</b> ANTHRACITE	<b>4K</b> 4000K	
<b>BI</b> WHITE		

ACCESSORIES

<p>STAMP POST ANCHOR PLATE L 128</p>  <p><b>5391</b></p>	<p>STAMP SPACER</p>  <p><b>5351</b></p>	<p>STAMP FIXING BRACKET</p>  <p><b>5360</b></p>	<p>STAMP 110 &amp; GLASS - BACKBOX</p>  <p><b>5358</b></p>
<p>ACCESSORIES WATERPROOF CONNECTOR</p>  <p><b>1941</b></p>	<p>ACCESSORIES WATERPROOF CONNECTOR</p>  <p><b>1944</b></p>	<p>ACCESSORIES 24V CONTROL GEAR</p>  <p><b>1924</b></p>	<p>ACCESSORIES 24V CONTROL GEAR</p>  <p><b>1925</b></p>

**STAMP** THE SERIES

