



Pole complete with luminaire
 Material: aluminium
 Diffuser: ultra-white opal tempered glass
 External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately
 Light source: LED unit
 Supplied with H05RN-F pre-wired cable (optional waterproof connections to be ordered separately)
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

Dimensions	128 x 44 x H 300 mm
Light source	LED
Wattage	6 W
Power supply	24 Vdc
Light source output	698 lm
System output	302 lm
System efficiency	50 lm/W
Color Rendering Index – CRI	80
LED energy class	F
LED lifetime	L70 B50 > 54.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class III
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	1.8 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	3K	3000K
AN	ANTHRACITE	4K	4000K
BI	WHITE		

ACCESSORIES

STAMP POST
ANCHOR PLATE L 128



5391

STAMP
SPACER



5351

STAMP
FIXING BRACKET



5360

STAMP
110 & GLASS - BACKBOX



5358

ACCESSORIES
WATERPROOF CONNECTOR



1941

ACCESSORIES
WATERPROOF CONNECTOR



1944

ACCESSORIES
24V DRIVER - 24W



1924

ACCESSORIES
24V DRIVER - 60W



1925