



Pole complete with luminaire

Material: aluminium

Diffuser: ultra-white opal tempered glass

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: LED unit

Supplied with H05RN-F pre-wired cable (optional waterproof connections to be ordered separately)

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

Dimensions	128 x 44 x H 600 mm
Light source	LED
Wattage	6 W
Power supply	24 Vdc
Light source output	698 lm
System output	302 lm
System efficiency	50 lm/W
Color Rendering Index – CRI	80
LED energy class	F
LED lifetime	L70 B50 > 54.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class III
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	2.2 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	3K	3000K
AN	ANTHRACITE	4K	4000K
BI	WHITE		

ACCESSORIES

<p>STAMP POST ANCHOR PLATE L 128</p>  <p>5391</p>	<p>STAMP SPACER</p>  <p>5351</p>	<p>STAMP FIXING BRACKET</p>  <p>5360</p>	<p>STAMP 110 & GLASS – BACKBOX</p>  <p>5358</p>
<p>ACCESSORIES WATERPROOF CONNECTOR</p>  <p>1941</p>	<p>ACCESSORIES WATERPROOF CONNECTOR</p>  <p>1944</p>	<p>ACCESSORIES 24V DRIVER – 24W</p>  <p>1924</p>	<p>ACCESSORIES 24V DRIVER – 60W</p>  <p>1925</p>