

Outdoor luminaire for pole installation

Material: dissipating upper disc in low copper content die-cast aluminium; the particular convex shape avoids water stagnation / Cone in low copper content die-cast aluminium; higher light diffusion in the aluminium grey finish, minimum upward light dispersion in the anthracite finish

Photo-etched polycarbonate diffuser to prevent horizontal glare and to grant high output downwards

Built-in driver

Light source: LED unit

Watertight wiring through the supplied cable that powers the integrated driver. Further M16 cable gland for additional wiring, positioned in the lower part of the closing cap in technopolymer

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- 24V 24V low voltage

Dimensions	Ø 152 x H 116 mm
Light source	LED
Wattage	12.5 W
Power supply	220-240 V 50/60 Hz
Light source output	1725 lm
System output	968 lm
System efficiency	77 lm/W
Color Rendering Index – CRI	80
LED energy class	D (3000K), D (4000K), E (2700K)
LED lifetime	L80 B20 > 80.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	1.6 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

- AG ALUMINIUM GREY
- ANAG ANTHRACITE + ALUMINIUM GREY
- AN ANTHRACITE
- AGAN ALUMINIUM GREY + ANTHRACITE

COLOUR TEMP.



- 27K 2700K
- 3K 3000K
- 4K 4000K

on request:


- CO CORTEN



COMPONENTS



ACCESSORIES



T-LUX THE SERIES

