



Outdoor luminaire for wall installation

Material: dissipating disc in low copper content die-cast aluminium / Cone in low copper content die-cast aluminium; its harmonious shape contains the wiring and guides the luminous flux towards the wall

Photo-etched polycarbonate diffuser to prevent side glare and to grant a homogeneous effect with 360° diffused light

Light source: mains voltage LED module, compatible with phase-cut dimmers

Compatible with beam limiter (code 5555)

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

**24V** 24V low voltage

Dimensions	Ø 152 x 82 mm
Light source	LED
Wattage	10 W
Power supply	220-240 V   50/60 Hz
Light source output	1200 lm
System output	607 lm
System efficiency	61 lm/W
Color Rendering Index – CRI	80
LED energy class	E (4000K), F (2700K), F (3000K)
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 09 (10 Joules)
Norms	EN 60598-1 +2-1
Weight	0.66 kg
Conformity	CE UK CA

## CODE OPTIONS

### FINISH

<b>AG</b>	ALUMINIUM GREY
<b>AN</b>	ANTHRACITE
<b>CO</b>	CORTEN
<b>BR</b>	BRONZE
<b>BI</b>	WHITE

### COLOUR TEMP.

<b>27K</b>	2700K
<b>3K</b>	3000K
<b>4K</b>	4000K

ACCESSORIES



T-LUX THE SERIES

