

Outdoor luminaire for wall/pole installation  
 Material: low copper content die-cast aluminium  
 Diffuser: ultra-white opal tempered glass  
 Built-in driver  
 Light source: 24V linear LED modules mounted on the dedicated heat sink to grant a homogeneous light distribution on the diffuser  
 Rear cable entry  
 Stainless steel cross-head screws  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D** Dimmable version
- 24V** 24V low voltage

Dimensions	<b>242 x 242 x 281 mm</b>
Light source	<b>LED</b>
Wattage	<b>34.5 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
System output	<b>1684 lm</b>
System efficiency	<b>49 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>D</b>
LED lifetime	<b>L80 B20 &gt; 80.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class II</b>
IP rating	<b>IP 65</b>
Impact resistance rating	<b>IK 08 (5 Joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>5 kg</b>
Conformity	<b>CE UK CA</b>

**CODE OPTIONS**


**FINISH**

- AG** ALUMINIUM GREY
- AN** ANTHRACITE

**COLOUR TEMP.**

- 3K** 3000K
- 4K** 4000K

ACCESSORIES



**TRIANGOLO** THE SERIES

