

Outdoor luminaire for wall/pole installation
 Material: low copper content die-cast aluminium
 Diffuser: ultra-white transparent tempered glass
 Built-in driver
 Light source: 16 power LEDs unit and 4 lenses STRADA 2x2 mounted on the dedicated heat sink / Symmetric and asymmetric optics
 Rear cable entry
 Stainless steel cross-head screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):
D Dimmable version

Dimensions	242 x 242 x 281 mm
Light source	LED
Wattage	56 W
Power supply	220-240 V 50/60 Hz
Light source output	5816 lm
System output	5003 lm
System efficiency	89 lm/W
Color Rendering Index – CRI	80
LED energy class	D
LED lifetime	L90 B10 > 100.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	5 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K


OPTIC

standard 100°

optional optics

BAT BATWING
25 25°

ACCESSORIES



TRIANGOLO THE SERIES

