

Outdoor luminaire for wall/pole installation
 Material: low copper content die-cast aluminium
 Diffuser: ultra-white opal tempered glass
 Driver + 3h emergency unit inside
 Light source: 24V linear LED modules mounted on the dedicated heat sink to grant a homogeneous light distribution on the diffuser
 Rear cable entry
 Stainless steel cross-head screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):


- D** Dimmable version
- 24V** 24V low voltage

Dimensions	242 x 242 x 281 mm
Light source	LED
Wattage	34.5 W
Power supply	220-240 V 50/60 Hz
System output	1684 lm
System efficiency	49 lm/W
Color Rendering Index – CRI	80
LED energy class	D
LED lifetime	L80 B20 > 80.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1 +2-22
Weight	5 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	3K	3000K
AN	ANTHRACITE	4K	4000K

ACCESSORIES



TRIANGOLO

THE SERIES

