

Outdoor luminaire for wall/pole installation
 Material: low copper content die-cast aluminium
 Diffuser: ultra-white opal tempered glass
 Driver + 3h emergency unit inside
 Light source: 24V linear LED modules mounted on the dedicated heat sink to grant a homogeneous light distribution on the diffuser
 Rear cable entry
 Stainless steel cross-head screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):


- D** Dimmable version
- 24V** 24V low voltage

| | |
|--|------------------------------|
| Dimensions | 242 x 242 x 281 mm |
| Light source | LED |
| Wattage | 34.5 W |
| Power supply | 220-240 V 50/60 Hz |
| System output | 1684 lm |
| System efficiency | 49 lm/W |
| Color Rendering Index – CRI | 80 |
| LED energy class | D |
| LED lifetime | L80 B20 > 80.000 h |
| Standard Deviation Color Matching (SDCM) | MacAdam step 3 |
| Electrical insulation class | Class II |
| IP rating | IP 65 |
| Impact resistance rating | IK 08 (5 Joules) |
| Norms | EN 60598-1 +2-1 +2-22 |
| Weight | 5 kg |
| Conformity | CE UK CA |

CODE OPTIONS

| FINISH | | COLOUR TEMP. | |
|-----------|----------------|--------------|-------|
| AG | ALUMINIUM GREY | 3K | 3000K |
| AN | ANTHRACITE | 4K | 4000K |

ACCESSORIES



TRIANGOLO THE SERIES

