



Outdoor luminaire for wall installation  
 Adjustable upwards or downwards  
 Material: housing and glass holding frame in low copper content die-cast aluminium  
 Diffuser: transparent tempered glass  
 Built-in driver  
 Light source: 4 LED units  
 Rear cable entry  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D Dimmable version

Dimensions	120 x 120 x 400 mm
Light source	LED
Multiple sources	4x
Wattage	26 W
Power supply	220-240 V   50/60 Hz
Light source output	3804 lm
System output	2868 lm
System efficiency	110 lm/W
Color Rendering Index – CRI	80
LED energy class	E
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	3.1 kg
Conformity	CE UK CA

### CODE OPTIONS

#### FINISH

**AG** ALUMINIUM GREY  
**NE** BLACK

#### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

#### OPTIC

**standard** 24°

optional optics

**ASY** ASYMMETRIC  
**16** 16°  
**60** 60°

ACCESSORIES



**VOLTO** THE SERIES

