



Outdoor luminaire for wall installation
 Adjustable upwards or downwards
 Material: housing and glass holding frame in low copper content die-cast aluminium
 Diffuser: transparent tempered glass
 Built-in driver
 Light source: 4 LED units
 Rear cable entry
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D Dimmable version

Dimensions	120 x 120 x 400 mm
Light source	LED
Multiple sources	4x
Wattage	26 W
Power supply	220-240 V 50/60 Hz
Light source output	3804 lm
System output	2868 lm
System efficiency	110 lm/W
Color Rendering Index – CRI	80
LED energy class	E
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	3.1 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
NE BLACK

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

OPTIC

standard 24°

optional optics

ASY ASYMMETRIC

16 16°

60 60°

ACCESSORIES



VOLTO THE SERIES

