



Outdoor luminaire for wall installation
Asymmetric reflector with double position
Material: low copper content die-cast aluminium
Ultra-white transparent tempered glass flush diffuser
Built-in driver
Light source: LED unit
Rear cable entry
Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

Dimensions	222 x 100 x 116 mm
Light source	LED
Multiple sources	2x
Wattage	22 W
Power supply	220-240 V 50/60 Hz
Light source output	2810 lm
System output	2300 lm
System efficiency	105 lm/W
Color Rendering Index – CRI	80
LED energy class	E (3000K), E (4000K), F (2700K)
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	2.2 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	27K	2700K
AN	ANTHRACITE	3K	3000K
CO	CORTEN	4K	4000K
BI	WHITE		

on request:



WASH

THE SERIES

