



421

Outdoor luminaire for wall installation
 Material: low copper content die-cast aluminium
 Opal tempered glass flush diffuser
 Built-in driver
 Light source: linear LED module
 Rear cable entry
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- E Emergency

Dimensions	421 x 70 x 71 mm
Light source	LED
Wattage	13 W
Power supply	220-240 V 50/60 Hz
Light source output	1629 lm
System output	977 lm
System efficiency	75 lm/W
Color Rendering Index – CRI	80
LED energy class	D
LED lifetime	L80 B20 > 60.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	2 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	27K	2700K
AN	ANTHRACITE	3K	3000K
CO	CORTEN	4K	4000K
BI	WHITE		

on request:

- BR BRONZE

WASH THE SERIES

