



Outdoor luminaire for wall installation  
 Material: low copper content die-cast aluminium  
 Opal tempered glass flush diffuser  
 Built-in driver  
 Light source: linear LED module  
 Rear cable entry  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- E Emergency

Dimensions	240 x 100 x 130 mm
Light source	LED
Wattage	9 W
Power supply	220-240 V   50/60 Hz
Light source output	1162 lm
System output	674 lm
System efficiency	75 lm/W
Color Rendering Index – CRI	80
LED energy class	D
LED lifetime	L80 B20 > 80.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	1.8 kg
Conformity	CE UK CA

### CODE OPTIONS

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	27K	2700K
AN	ANTHRACITE	3K	3000K
CO	CORTEN	4K	4000K
BI	WHITE		

on request:

- BR BRONZE

WASH THE SERIES

