



Outdoor luminaire for wall installation
 Asymmetric reflector with double position
 Material: low copper content die-cast aluminium
 Ultra-white transparent tempered glass flush diffuser
 Built-in driver
 Light source: LED unit
 Rear cable entry
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

Dimensions	240 x 100 x 130 mm
Light source	LED
Multiple sources	2x
Wattage	22 W
Power supply	220-240 V 50/60 Hz
Light source output	2810 lm
System output	2300 lm
System efficiency	105 lm/W
Color Rendering Index – CRI	80
LED energy class	E (3000K), E (4000K), F (2700K)
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	2 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH	COLOUR TEMP.
AG ALUMINIUM GREY	27K 2700K
AN ANTHRACITE	3K 3000K
CO CORTEN	4K 4000K
BI WHITE	

on request:



WASH THE SERIES

