



Outdoor luminaire for wall installation  
Asymmetric reflector with double position  
Material: low copper content die-cast aluminium  
Ultra-white transparent tempered glass flush diffuser  
Built-in driver  
Light source: LED unit  
Rear cable entry  
Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

Dimensions	240 x 100 x 130 mm
Light source	LED
Wattage	11 W
Power supply	220-240 V   50/60 Hz
Light source output	1405 lm
System output	1150 lm
System efficiency	105 lm/W
Color Rendering Index – CRI	80
LED energy class	E (3000K), E (4000K), F (2700K)
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	1.8 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

**AG** ALUMINIUM GREY  
**AN** ANTHRACITE  
**CO** CORTEN  
**BI** WHITE

COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

on request:

**BR** BRONZE

WASH

THE SERIES

