



Outdoor luminaire for wall installation  
 Material: low copper content die-cast aluminium  
 Opal tempered glass flush diffuser  
 Built-in driver  
 Light source: linear LED module  
 Rear cable entry  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- E Emergency

Dimensions	530 x 70 x 81 mm
Light source	LED
Multiple sources	2x
Wattage	26 W
Power supply	220-240 V   50/60 Hz
Light source output	3258 lm
System output	1954 lm
System efficiency	75 lm/W
Color Rendering Index – CRI	80
LED energy class	D
LED lifetime	L80 B20 > 60.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	1.9 kg
Conformity	CE UK CA

### CODE OPTIONS

#### FINISH

**AG** ALUMINIUM GREY  
**AN** ANTHRACITE  
**CO** CORTEN  
**BI** WHITE

#### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

on request:

**BR** BRONZE

WASH THE SERIES

