

Outdoor ground/wall recessed luminaire

Max. load pressure 2.300 kg (in-ground box + luminaire + covering flange together for drive-over use)

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: LED unit / Adjustable optics ±15°

Pre-wired with 0,5 m H07RN-F buriable cable (optional waterproof connections to be ordered separately - codes 1941-1942-1944)

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

Dimensions	Ø 157 x H 129 mm
Light source	LED
Wattage	16 W
Power supply	220-240 V   50/60 Hz
Light source output	2643 lm
System output	1819 lm
System efficiency	114 lm/W
Color Rendering Index – CRI	80
LED energy class	E
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-13
Weight	1.4 kg
Conformity	CE UK CA

CODE OPTIONS

COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

OPTIC


**standard** 38°  
optional optics  
**18** 18°  
**90** 90°

# PASSUM UP Ø 180 aluminium LED 16W

1433


## COMPONENTS

PASSUM  
Ø 180 IN-GROUND BOX




1431

PASSUM UP  
Ø 180 ALUMINIUM ROUND  
FLANGE



1531

PASSUM UP  
Ø 180 STAINLESS STEEL  
ROUND FLANGE



1532


PASSUM UP  
Ø 180 STAINLESS STEEL  
SQUARE FLANGE



1533

## ACCESSORIES

ACCESSORIES  
WATERPROOF CONNECTOR



1941

ACCESSORIES  
WATERPROOF CONNECTOR



1944

ACCESSORIES  
WATERPROOF CONNECTOR



1942

PASSUM UP  
Ø 180 ANTI-GLARE LOUVRE



1971

## PASSUM UP THE SERIES

