


Outdoor luminaire with diffused light for pole installation  
 Material: die-cast aluminium  
 Diffuser: UV resistant polycarbonate  
 Light source: mains voltage LED module, compatible with phase-cut dimmers  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

Dimensions	<b>74 x 153 x 52 mm</b>
Light source	<b>LED</b>
Wattage	<b>8 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>835 lm</b>
System output	<b>423 lm</b>
System efficiency	<b>53 lm/W</b>
Color Rendering Index – CRI	<b>≥80</b>
LED energy class	<b>F (3000K), F (4000K), G (2700K)</b>
LED lifetime	<b>L70 B10 45.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class I</b>
IP rating	<b>IP 65</b>
Impact resistance rating	<b>IK 10 (20 joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>0.36 kg</b>
Conformity	<b>CE UK CA</b>



FIXTURES RELATED



CODE OPTIONS

FINISH

<b>AG</b>	ALUMINIUM GREY
<b>AN</b>	ANTHRACITE
<b>CO</b>	CORTEN
<b>BR</b>	BRONZE

COLOUR TEMP.

<b>27K</b>	2700K
<b>3K</b>	3000K
<b>4K</b>	4000K