



Outdoor wall steplight luminaire

Minimum thickness for surface installation / Recessed installation flush with the wall using backbox optional accessory

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Light source: mains voltage LED module, compatible with phase-cut dimmers

Rear cable entry

Stainless steel screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):
24V 24V low voltage

Dimensions	Ø 90 x H 41 mm
Light source	LED
Wattage	4 W
Power supply	220-240 V 50/60 Hz
Light source output	380 lm
System output	50 lm
System efficiency	12 lm/W
Color Rendering Index – CRI	≥80
LED energy class	F
LED lifetime	L70 B10 45.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	0.3 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH		COLOUR TEMP.	
AN	ANTHRACITE	27K	2700K
BI	WHITE	3K	3000K
		4K	4000K

on request:

AG	ALUMINIUM GREY
CO	CORTEN
BR	BRONZE



ACCESSORIES

