



Outdoor luminaire for wall installation  
 Material: low copper content die-cast aluminium  
 Ultra-white transparent tempered glass flush diffuser  
 Built-in driver  
 Light source: LED unit  
 Rear cable entry  
 Stainless steel screws  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

**D** Dimmable version  
**24V** 24V low voltage

Dimensions	95 x 120 x H 123 mm
Light source	LED
Wattage	8 W
Power supply	100-240 V   50/60 Hz
Light source output	951 lm
System output	840 lm
System efficiency	105 lm/W
Color Rendering Index – CRI	80
LED energy class	E
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	1.2 kg
Conformity	CE UK CA

## CODE OPTIONS

### FINISH

**AN** ANTHRACITE  
**BI** WHITE

on request:

**AG** ALUMINIUM GREY  
**CO** CORTEN  
**BR** BRONZE

### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

### OPTIC

**standard** 24°

optional optics

**16** 16°  
**60** 60°