



Outdoor luminaire for wall installation
 Material: low copper content die-cast aluminium
 Ultra-white transparent tempered glass flush diffuser
 Built-in driver
 Light source: LED unit
 Rear cable entry
 Stainless steel screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):
 D Dimmable version

Dimensions	136 x 161 x H 153 mm
Light source	LED
Wattage	19 W
Power supply	220-240 V 50/60 Hz
Light source output	2761 lm
System output	2350 lm
System efficiency	124 lm/W
Color Rendering Index – CRI	80
LED energy class	E
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	2.1 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AN ANTHRACITE
BI WHITE

on request:

AG ALUMINIUM GREY
CO CORTEN
BR BRONZE

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

OPTIC

standard 15°

optional optics

35 35°
90 90°