



Outdoor luminaire for ceiling installation  
 Material: low copper content die-cast aluminium  
 Ultra-white transparent tempered glass flush diffuser  
 Built-in driver  
 Light source: LED unit  
 Rear cable entry  
 Stainless steel screws  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

**D** Dimmable version

Dimensions	<b>Ø 134 x H 141 mm</b>
Light source	<b>LED</b>
Wattage	<b>19 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>2761 lm</b>
System output	<b>2350 lm</b>
System efficiency	<b>123 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>E</b>
LED lifetime	<b>L80 B10 86.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class I</b>
IP rating	<b>IP 65</b>
Impact resistance rating	<b>IK 08 (5 Joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>1.8 kg</b>
Conformity	<b>CE UK CA</b>

## CODE OPTIONS

### FINISH

**AN** ANTHRACITE  
**BI** WHITE

on request:

**AG** ALUMINIUM GREY  
**CO** CORTEN  
**BR** BRONZE

### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

### OPTIC

**standard** 15°

optional optics

**35** 35°  
**90** 90°