



Outdoor luminaire for ceiling installation  
 Minimum thickness for surface installation / Recessed installation flush with the wall using backbox optional accessory  
 Material: low copper content die-cast aluminium  
 Ultra-white transparent tempered glass flush diffuser  
 Light source: mains voltage LED module, compatible with phase-cut dimmers  
 Rear cable entry  
 Stainless steel screws  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):  
**24V** 24V low voltage

Dimensions	Ø 90 x H 41 mm
Light source	LED
Wattage	4 W
Power supply	220-240 V   50/60 Hz
Light source output	380 lm
System output	130 lm
System efficiency	32 lm/W
Color Rendering Index – CRI	≥80
LED energy class	F
LED lifetime	L70 B10 45.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	0.32 kg
Conformity	CE UK CA

### CODE OPTIONS

#### FINISH

**AN** ANTHRACITE  
**BI** WHITE

on request:

**AG** ALUMINIUM GREY  
**CO** CORTEN  
**BR** BRONZE

#### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

#### OPTIC

**standard** 40°  
 optional optics  
**12** 12°



ACCESSORIES

