



Outdoor luminaire for ceiling installation
 Minimum thickness for surface installation / Recessed installation flush with the wall using backbox optional accessory
 Material: low copper content die-cast aluminium
 Ultra-white transparent tempered glass flush diffuser
 Light source: mains voltage LED module, compatible with phase-cut dimmers
 Rear cable entry
 Stainless steel screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):
24V 24V low voltage

Dimensions	Ø 90 x H 41 mm
Light source	LED
Wattage	4 W
Power supply	220-240 V 50/60 Hz
Light source output	380 lm
System output	130 lm
System efficiency	32 lm/W
Color Rendering Index – CRI	≥80
LED energy class	F
LED lifetime	L70 B10 45.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	0.32 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AN ANTHRACITE
BI WHITE

on request:

AG ALUMINIUM GREY
CO CORTEN
BR BRONZE

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

OPTIC

standard 40°

optional optics

12 12°



ACCESSORIES

