
goccia ILLUMINAZIONE

DART Ø 23 LED 1.3W – MAX 350MA

1623





Outdoor ground/wall/ceiling recessed luminaire

Material: housing and covering ring in anodized anticorodal turned aluminium for OS and ON finishes; housing in anodized anticorodal turned aluminum and covering ring in AISI 316L stainless steel for IN finish

Diffuser: ultra-white transparent tempered glass

External CC (constant current) 350 mA driver for series connection, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: constant current LED module

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN version

On request versions (additional code):
MT7 7 m cable length

Dimensions	Ø 23 x H 60 mm
Light source	LED
Wattage	1.3 W
Power supply	max 350 mA
Light source output	116 lm
System output	86 lm
System efficiency	66 lm/W
Color Rendering Index – CRI	80
LED energy class	F
Electrical insulation class	Class III
IP rating	IP 65/67
Impact resistance rating	IK 08 (5 Joules)
Diffuser contact temperature	≤ 40°C
Norms	EN 60598-1 +2-13
Weight	0.09 kg
Conformity	CE UKCA

CODE OPTIONS

FINISH

OS	NATURAL ANODIZATION
ON	BLACK ANODIZATION
IN	STAINLESS STEEL

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K

OPTIC

standard	35°

optional optics

15	15°
60	60°

DART Ø 23 LED 1.3W – MAX 350MA

1623

ACCESSORIES

DART
Ø 23 CYLINDRICAL RECESSED BOX



1621

DART
Ø 23 RECESSED BOX



1622

DART
Ø 23 CLIP



1620

ACCESSORIES
CC 350 MA DRIVER – 3,6W

1975

ACCESSORIES
CC 350 MA DRIVER – 14W

1976