


DART Ø 23 OPAL LED 1.3W - MAX 350MA

1624









Outdoor ground/wall/ceiling recessed luminaire

Material: housing and covering ring in anodized anticorodal turned aluminium for OS and ON finishes; housing in anodized anticorodal turned aluminum and covering ring in AISI 316L stainless steel for IN finish

Diffuser: ultra-white opal tempered glass

External CC (constant current) 350 mA driver for series connection, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: constant current LED module

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN version

On request versions (additional code):

MT7 7 m cable length

Diffuser contact temperature	≤ 40°C	
Dimensions	Ø 23 x H 60 mm	
Light Source	LED	
Power	1.3 W	
Voltage/Frequency	max 350 mA	
LUMEN OUTPUT	15 lm	
System efficiency	11 lm/W	
Color Rendering Index - CRI	80	
LED energy class	F	
Electrical insulation class	Class III	
IP rating	IP 65/67	
Impact resistance rating	IK 08 (5 Joules)	
Norms	EN 60598-1 +2-13	
Weight	0.09 kg	
Certifications	C€ FR	

CODE OPTIONS

FINISH		COLOUR TEMP.	
ON	BLACK ANODIZATION	27K	2700K
OS	NATURAL ANODIZATION	3K	3000K
IN	STAINLESS STEEL	4K	4000K





Goccia Illuminazione srl



DART Ø 23 OPAL LED 1.3W - MAX 350MA

1624

ACCESSORIES

