



Outdoor ground/wall/ceiling recessed luminaire

Material: housing and covering ring in anodized anticorodal turned aluminium for OS and ON finishes; housing in anodized anticorodal turned aluminum and covering ring in AISI 316L stainless steel for IN finish

Diffuser: ultra-white opal tempered glass

External CC (constant current) 350 mA driver for series connection, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: constant current LED module

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN version

On request versions (additional code):

MT7 7 m cable length

#### Dimensions

Ø 35 x H 81 mm

Light source	LED
Wattage	2 W
Power supply	350 mA
Light source output	116 lm
System output	13 lm
System efficiency	7 lm/W
Color Rendering Index – CRI	80
LED energy class	F
Electrical insulation class	Class III
IP rating	IP 65/67
Impact resistance rating	IK 08 (5 Joules)
Diffuser contact temperature	≤ 40°C
Norms	EN 60598-1 +2-13
Weight	0.15 kg
Conformity	CE UKCA

#### CODE OPTIONS

##### FINISH

**OS** NATURAL ANODIZATION  
**ON** BLACK ANODIZATION  
**IN** STAINLESS STEEL

##### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

**DART Ø 35 OPAL** LED 2W – 350MA

**1635**



ACCESSORIES

