

Outdoor ground/wall/ceiling recessed luminaire

Material: housing and covering ring in anodized anticorodal turned aluminium for OS and ON finishes; housing in anodized anticorodal turned aluminum and covering ring in AISI 316L stainless steel for IN finish

Diffuser: ultra-white opal tempered glass

External CC (constant current) 350 mA driver for series connection, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: constant current LED module

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN version

On request versions (additional code):

MT7 7 m cable length

Diffuser contact temperature	≤ 40°C
Dimensions	Ø 35 x H 81 mm
Light Source	LED
Power	2 W
Voltage/Frequency	350 mA
LUMEN OUTPUT	13 lm
System efficiency	6 lm/W
Color Rendering Index – CRI	80
LED energy class	F
Electrical insulation class	Class III
IP rating	IP 65/67
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-13
Weight	0.15 kg
Certifications	CE UK CA

CODE OPTIONS



FINISH

ON	BLACK ANODIZATION
OS	NATURAL ANODIZATION
IN	STAINLESS STEEL

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K

ACCESSORIES

<p>DART Ø 35-40 CYLINDRICAL RECESSED BOX</p>  <p>1631</p>	<p>DART Ø 35-40 RECESSED BOX</p>  <p>1632</p>	<p>DART Ø 35 CLIP</p>  <p>1630</p>
--	--	---