

DART Ø 35 OPAL LED 2W - 350MA

1635







Outdoor ground/wall/ceiling recessed luminaire

Material: housing and covering ring in anodized anticorodal turned aluminium for OS and ON finishes; housing in anodized anticorodal turned aluminum and covering ring in AISI 316L stainless steel for IN finish

Diffuser: ultra-white opal tempered glass

External CC (constant current) 350 mA driver for series connection, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: constant current LED module

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN version

On request versions (additional code):

MT7 7 m cable length

Diffuser contact temperature	≤ 40°C
Dimensions	Ø 35 x H 81 mm
Light Source	LED
Power	2 W
Voltage/Frequency	350 mA
LUMEN OUTPUT	13 lm
System efficiency	6 lm/W
Color Rendering Index - CRI	80
LED energy class	F
Electrical insulation class	Class III
IP rating	IP 65/67
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-13
Weight	0.15 kg
Certifications	C€ EŘ

CODE OPTIONS

FINISH		COLOU	COLOUR TEMP.	
ON	BLACK ANODIZATION	27K	2700K	
OS	NATURAL ANODIZATION	3K	3000K	
IN	STAINLESS STEEL	4K	4000K	





Goccia Illuminazione srl



DART Ø 35 OPAL LED 2W - 350MA

1635

ACCESSORIES









