


### **DART Ø 35 OPAL IFD 2W - 24V**

#### 1636









Outdoor ground/wall/ceiling recessed luminaire

Material: housing and covering ring in anodized anticorodal turned aluminium for OS and ON finishes; housing in anodized anticorodal turned aluminum and covering ring in AISI 316L stainless steel for IN finish

Diffuser: ultra-white opal tempered glass

PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: LED module Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN

On request versions (additional code):

MT7 7 m cable length

| ≤ 40°C           | Diffuser contact temperature |
|------------------|------------------------------|
| Ø 35 x H 81 mm   | Dimensions                   |
| LED              | Light Source                 |
| 2 W              | Power                        |
| 24V DC           | Voltage/Frequency            |
| 13 lm            | LUMEN OUTPUT                 |
| 6 lm/W           | System efficiency            |
| 80               | Color Rendering Index - CRI  |
| F                | LED energy class             |
| Class III        | Electrical insulation class  |
| IP 65/67         | IP rating                    |
| IK 08 (5 Joules) | Impact resistance rating     |
| EN 60598-1 +2-13 | Norms                        |
| C€ FR            | Certifications               |

# **CODE OPTIONS**

| FINISH                        | COLOUR | R TEMP. |
|-------------------------------|--------|---------|
| <b>ON</b> BLACK ANODIZATION   | 27K    | 2700K   |
| <b>OS</b> NATURAL ANODIZATION | 3K     | 3000K   |
| IN STAINLESS STEEL            | 4K     | 4000K   |





Goccia Illuminazione srl

#### DART Ø 35 OPAL LED 2W - 24V

# 9

# 1636

#### **ACCESSORIES**















