

DART Ø 55 - 24V LED 4W - 24V

1654







Outdoor ground/wall/ceiling recessed luminaire

Material: housing and covering ring in anodized anticorodal turned aluminium for OS and ON finishes; housing in anodized anticorodal turned aluminum and covering ring in AISI 316L stainless steel for IN finish

Diffuser: ultra-white transparent tempered glass

PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: LED unit

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN

On request versions (additional code):

MT7 7 m cable length

≤ 40°C	Diffuser contact temperature
Ø 55 x H 82 mm	Dimensions
LED	Light Source
4 W	Power
24V DC	Voltage/Frequency
355 lm	LUMEN OUTPUT
89 lm/W	System efficiency
80	Color Rendering Index – CRI
E (3000K), E (4000K), F (2700K)	LED energy class
Class III	Electrical insulation class
IP 65/67	IP rating
IK 08 (5 Joules)	Impact resistance rating
EN 60598-1 +2-13	Norms
0.3 kg	Weight
(Certifications

CODE OPTIONS

FINISH		COLOUR TEMP.		OPTIC	
ON	BLACK ANODIZATION	27K	2700K	standard	30
OS	NATURAL ANODIZATION	3K	3000K	optional optics	
IN	STAINLESS STEEL	4K	4000K		
				10	10
				54	5/







1654

















