



Outdoor ground/wall/ceiling recessed luminaire

Material: housing and covering ring in anodized anticorrosive aluminium for OS and ON finishes; housing in anodized anticorrosive aluminium and covering ring in AISI 316L stainless steel for IN finish

Diffuser: ultra-white transparent tempered glass

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: LED unit

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN version

On request versions (additional code):

**MT7** 7 m cable length

Dimensions	<b>Ø 55 x H 82 mm</b>
Light source	<b>LED</b>
Wattage	<b>4 W</b>
Power supply	<b>24 Vdc</b>
Light source output	<b>470 lm</b>
System output	<b>355 lm</b>
System efficiency	<b>89 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>E (3000K), E (4000K), F (2700K)</b>
LED lifetime	<b>L80 B10 86.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class III</b>
IP rating	<b>IP 65/67</b>
Impact resistance rating	<b>IK 08 (5 Joules)</b>
Diffuser contact temperature	<b>≤ 40°C</b>
Norms	<b>EN 60598-1 +2-13</b>
Weight	<b>0.3 kg</b>
Conformity	<b>CE UK CA</b>

## CODE OPTIONS

### FINISH

**OS** NATURAL ANODIZATION  
**ON** BLACK ANODIZATION  
**IN** STAINLESS STEEL

### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

### OPTIC

**standard** 30°  
optional optics  
**10** 10°  
**54** 54°

# DART Ø 55 – 24V LED 4W – 24V

## 1654

### ACCESSORIES

ACCESSORIES  
24V DRIVER – 24W




1924

ACCESSORIES  
24V DRIVER – 60W



1925

DART  
Ø 55-60 24V CYLINDRICAL  
RECESSED BOX




1657

DART  
Ø 55-60 24V RECESSED BOX



1658

DART  
Ø 55 CLIP



1650

ACCESSORIES  
PWM DRIVER



1953