



Outdoor ground/wall/ceiling recessed luminaire

Material: housing and covering ring in anodized anticorrosive aluminium for OS and ON finishes; housing in anodized anticorrosive aluminium and covering ring in AISI 316L stainless steel for IN finish

Diffuser: ultra-white opal tempered glass

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: LED unit

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN version

On request versions (additional code):

MT7 7 m cable length

| | |
|--|--|
| Dimensions | Ø 55 x H 82 mm |
| Light source | LED |
| Wattage | 4 W |
| Power supply | 24 Vdc |
| Light source output | 470 lm |
| System output | 44 lm |
| System efficiency | 11 lm/W |
| Color Rendering Index – CRI | 80 |
| LED energy class | E (3000K), E (4000K), F (2700K) |
| LED lifetime | L80 B10 86.000 h |
| Standard Deviation Color Matching (SDCM) | MacAdam step 3 |
| Electrical insulation class | Class III |
| IP rating | IP 65/67 |
| Impact resistance rating | IK 08 (5 Joules) |
| Diffuser contact temperature | ≤ 40°C |
| Norms | EN 60598-1 +2-13 |
| Weight | 0.45 kg |
| Conformity | CE UK CA |

CODE OPTIONS

FINISH

OS NATURAL ANODIZATION
ON BLACK ANODIZATION
IN STAINLESS STEEL

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

DART Ø 55 OPAL – 24V LED 4W – 24V

1656

ACCESSORIES

ACCESSORIES
24V DRIVER – 24W




1924

ACCESSORIES
24V DRIVER – 60W




1925

DART
Ø 55-60 24V CYLINDRICAL
RECESSED BOX




1657

DART
Ø 55-60 24V RECESSED BOX



1658

DART
Ø 55 CLIP



1650

ACCESSORIES
PWM DRIVER



1953