


DART Ø 55 OPAL - 24V IFD 4W - 24V 1656







Outdoor ground/wall/ceiling recessed luminaire

Material: housing and covering ring in anodized anticorodal turned aluminium for OS and ON finishes; housing in anodized anticorodal turned aluminum and covering ring in AISI 316L stainless steel for IN finish

Diffuser: ultra-white opal tempered glass

PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: LED unit

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN version

On request versions (additional code):

MT7 7 m cable length

≤ 40°C	Diffuser contact temperature
Ø 55 x H 82 mm	Dimensions
LED	Light Source
4 W	Power
24V DC	Voltage/Frequency
44 lm	LUMEN OUTPUT
11 lm/W	System efficiency
80	Color Rendering Index – CRI
E (3000K), E (4000K), F (2700K)	LED energy class
Class III	Electrical insulation class
IP 65/67	IP rating
IK 08 (5 Joules)	Impact resistance rating
EN 60598-1 +2-13	Norms
0.45 kg	Weight
C€ FR	Certifications

CODE OPTIONS

FINISH		COLOUR TEMP.	
ON	BLACK ANODIZATION	27K	2700K
os	NATURAL ANODIZATION	3K	3000K
IN	STAINLESS STEEL	4K	4000K





Goccia Illuminazione srl

DART Ø 55 OPAL - 24V LED 4W - 24V

1656

ACCESSORIES















