



Outdoor ground/wall/ceiling recessed luminaire

Material: housing and covering ring in anodized anticorrosive aluminium for OS and ON finishes; housing in anodized anticorrosive aluminium and covering ring in AISI 316L stainless steel for IN finish

Diffuser: ultra-white opal tempered glass

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: LED unit

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN version

On request versions (additional code):

MT7 7 m cable length

Dimensions	Ø 55 x H 82 mm
Light source	LED
Wattage	4 W
Power supply	24 Vdc
Light source output	470 lm
System output	44 lm
System efficiency	11 lm/W
Color Rendering Index – CRI	80
LED energy class	E (3000K), E (4000K), F (2700K)
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class III
IP rating	IP 65/67
Impact resistance rating	IK 08 (5 Joules)
Diffuser contact temperature	≤ 40°C
Norms	EN 60598-1 +2-13
Weight	0.45 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

OS NATURAL ANODIZATION
ON BLACK ANODIZATION
IN STAINLESS STEEL

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

DART Ø 55 OPAL – 24V LED 4W – 24V

1656

ACCESSORIES

ACCESSORIES
24V DRIVER – 24W




1924

ACCESSORIES
24V DRIVER – 60W




1925

DART
Ø 55-60 24V CYLINDRICAL
RECESSED BOX




1657

DART
Ø 55-60 24V RECESSED BOX



1658

DART
Ø 55 CLIP



1650

ACCESSORIES
PWM DRIVER



1953