



Outdoor ground/wall/ceiling recessed luminaire

Material: housing and covering ring in anodized anticorrosive turned aluminium for OS and ON finishes; housing in anodized anticorrosive turned aluminium and covering ring in AISI 316L stainless steel for IN finish

Diffuser: ultra-white opal tempered glass

Built-in driver

Light source: LED unit

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN version

On request versions (additional code):

MT7 7 m cable length

Dimensions	Ø 55 x H 122 mm
Light source	LED
Wattage	4 W
Power supply	220-240 V 50/60 Hz
Light source output	470 lm
System output	44 lm
System efficiency	11 lm/W
Color Rendering Index – CRI	80
LED energy class	E (3000K), E (4000K), F (2700K)
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 08 (5 Joules)
Diffuser contact temperature	≤ 40°C
Norms	EN 60598-1 +2-13
Weight	0.47 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

OS NATURAL ANODIZATION
ON BLACK ANODIZATION
IN STAINLESS STEEL

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K



ACCESSORIES

