

Outdoor ground/wall recessed luminaire

Material: housing and closing cap in anodized anticorrosive turned aluminium for OS and ON finishes; housing in anodized anticorrosive turned aluminum and closing cap in AISI 316L stainless steel for IN finish

Diffuser: UV resistant polycarbonate

External CC (constant current) 350 mA driver for series connection, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: constant current LED module / Side emitter optic to direct the light laterally

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN version

On request versions (additional code):

MT7 7 m cable length

Dimensions	Ø 40 x H 90 x H1 14 mm
Light source	LED
Wattage	2 W
Power supply	350 mA
Light source output	116 lm
System output	20 lm
System efficiency	10 lm/W
Color Rendering Index – CRI	80
LED energy class	F
Electrical insulation class	Class III
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Diffuser contact temperature	≤ 40°C
Norms	EN 60598-1 +2-13
Conformity	CE UK CA

CODE OPTIONS

FINISH

OS NATURAL ANODIZATION
ON BLACK ANODIZATION
IN STAINLESS STEEL

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

DART SIDE Ø 40 1x LED 2W – 350MA

1640

ACCESSORIES

DART
Ø 35-40 CYLINDRICAL
RECESSED BOX




1631

DART
Ø 35-40 RECESSED BOX




1632

ACCESSORIES
CC 350 MA DRIVER – 3,6W



1975

ACCESSORIES
CC 350 MA DRIVER – 14W



1976