


DART SIDE Ø 40 1x IFD 2W - 24V

1641







Outdoor ground/wall recessed luminaire

Material: housing and closing cap in anodized anticorodal turned aluminium for OS and ON finishes; housing in anodized anticorodal turned aluminum and closing cap in AISI 316L stainless steel for IN finish

Diffuser: UV resistant polycarbonate

PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: LED module / Side emitter optic to direct the light laterally

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN version

On request versions (additional code):

MT7 7 m cable length

≤	40°C
Ø 40 x H 90 x H1 14	4 mm
	LED
	2 W
24	4V DC
	20 lm
10	lm/W
	80
	F
Cla	ass III
IP 6	55/67
IK 10 (20 jo	oules)
EN 60598-1 +	+2-13
C	:€ FR

CODE OPTIONS

FINISH		COLOU	JR TEMP.
ON	BLACK ANODIZATION	27K	2700K
os	NATURAL ANODIZATION	3K	3000K
IN	STAINLESS STEEL	4K	4000K





DART SIDE Ø 40 1x LED 2W - 24V

9

1641

ACCESSORIES















Goccia Illuminazione srl