



Outdoor ground/wall recessed luminaire

Material: housing and closing cap in anodized anticorodal turned aluminium for OS and ON finishes; housing in anodized anticorodal turned aluminum and closing cap in AISI 316L stainless steel for IN finish

Diffuser: UV resistant polycarbonate

PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: LED module / Side emitter optic to direct the light laterally

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN version

On request versions (additional code):

MT7 7 m cable length

Diffuser contact temperature	≤ 40°C
Dimensions	Ø 40 x H 90 x H1 14 mm
Light Source	LED
Power	2 W
Voltage/Frequency	24V DC
LUMEN OUTPUT	20 lm
System efficiency	10 lm/W
Color Rendering Index – CRI	80
LED energy class	F
Electrical insulation class	Class III
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-13
Certifications	CE UK CA

CODE OPTIONS

FINISH

ON	BLACK ANODIZATION
OS	NATURAL ANODIZATION
IN	STAINLESS STEEL

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K



ACCESSORIES

ACCESSORIES
24V CONTROL GEAR



1924

ACCESSORIES
24V CONTROL GEAR



1925

DART
Ø 35-40 CYLINDRICAL
RECESSED BOX



1631

DART
Ø 35-40 RECESSED BOX



1632

ACCESSORIES
PWM DRIVER



1953