


DART SIDE Ø 40 2x LED 2W - 350MA

1642







Outdoor ground/wall recessed luminaire

Material: housing and closing cap in anodized anticorodal turned aluminium for OS and ON finishes; housing in anodized anticorodal turned aluminum and closing cap in AISI 316L stainless steel for IN finish

Diffuser: UV resistant polycarbonate

External CC (constant current) 350 mA driver for series connection, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: constant current LED module / Side emitter optic to direct the light laterally

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN

On request versions (additional code):

MT7 7 m cable length

Diffuser contact temperature	≤ 40°C Ø 40 x H 90 x H1 14 mm		
Dimensions			
Light Source	LED		
Power	2 W		
Voltage/Frequency	350 mA		
LUMEN OUTPUT	40 lm		
System efficiency	20 lm/W		
Color Rendering Index - CRI	80		
LED energy class	F		
Electrical insulation class	Class III		
IP rating	IP 65/67		
Impact resistance rating	IK 10 (20 joules)		
Norms	EN 60598-1 +2-13		
Certifications	C€ FR		

CODE OPTIONS

FINISH		COLOUR TEMP.	
ON	BLACK ANODIZATION	27K	2700K
os	NATURAL ANODIZATION	3K	3000K
IN	STAINLESS STEEL	4K	4000K

Goccia Illuminazione srl

via E.Fermi 59/65 - 25020 Poncarale (BS) Italy +39 030 2640761 - info@www.goccia.it









DART SIDE Ø 40 2x LED 2W - 350MA

1642

ACCESSORIES

