



Outdoor ground/wall recessed luminaire

Material: housing and closing cap in anodized anticorodal turned aluminium for OS and ON finishes; housing in anodized anticorodal turned aluminum and closing cap in AISI 316L stainless steel for IN finish

Diffuser: UV resistant polycarbonate

External CC (constant current) 350 mA driver for series connection, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: constant current LED module / Side emitter optic to direct the light laterally

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN version

On request versions (additional code):

MT7 7 m cable length

Dimensions

Ø 40 x H 90 x H1 14 mm

Light source	LED
Wattage	2 W
Power supply	350 mA
Light source output	116 lm
System output	40 lm
System efficiency	20 lm/W
Color Rendering Index – CRI	80
LED energy class	F
Electrical insulation class	Class III
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Diffuser contact temperature	≤ 40°C
Norms	EN 60598-1 +2-13
Conformity	CE UKCA

CODE OPTIONS

FINISH

OS	NATURAL ANODIZATION
ON	BLACK ANODIZATION
IN	STAINLESS STEEL

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K

DART SIDE Ø 40 2x LED 2W – 350MA

1642



ACCESSORIES

