

Outdoor ground/wall recessed luminaire

Material: housing and closing cap in anodized anticorrosive turned aluminium for OS and ON finishes; housing in anodized anticorrosive turned aluminum and closing cap in AISI 316L stainless steel for IN finish

Diffuser: UV resistant polycarbonate

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: LED module / Side emitter optic to direct the light laterally

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN version

On request versions (additional code):

MT7 7 m cable length

Dimensions	Ø 60 x H 97 x H1 20 mm
Light source	LED
Wattage	5 W
Power supply	24 Vdc
Light source output	520 lm
System output	135 lm
System efficiency	27 lm/W
Color Rendering Index – CRI	80
LED energy class	E (3000K), E (4000K), F (2700K)
Electrical insulation class	Class III
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-13
Weight	0.54 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

OS NATURAL ANODIZATION
ON BLACK ANODIZATION
IN STAINLESS STEEL

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

DART SIDE Ø 60 1x – 24V LED 5W – 24V

1662

ACCESSORIES

ACCESSORIES
24V DRIVER – 24W




1924

ACCESSORIES
24V DRIVER – 60W




1925

DART
Ø 55-60 24V CYLINDRICAL
RECESSED BOX



1657

DART
Ø 55-60 24V RECESSED BOX



1658

ACCESSORIES
PWM DRIVER



1953