



Outdoor ground/wall recessed luminaire

Material: housing and closing cap in anodized anticorodal turned aluminium for OS and ON finishes; housing in anodized anticorodal turned aluminum and closing cap in AISI 316L stainless steel for IN finish

Diffuser: UV resistant polycarbonate

Built-in driver

Light source: LED module / Side emitter optic to direct the light laterally

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN version

On request versions (additional code):

**MT7** 7 m cable length

Dimensions	<b>Ø 60 x H 137 x H1 20 mm</b>
Light source	<b>LED</b>
Wattage	<b>5 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>520 lm</b>
System output	<b>270 lm</b>
System efficiency	<b>54 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>E (3000K), E (4000K), F (2700K)</b>
Electrical insulation class	<b>Class I</b>
IP rating	<b>IP 65/67</b>
Impact resistance rating	<b>IK 10 (20 joules)</b>
Norms	<b>EN 60598-1 +2-13</b>
Conformity	<b>CE UK ENEC</b>

## CODE OPTIONS

### FINISH

<b>OS</b>	NATURAL ANODIZATION
<b>ON</b>	BLACK ANODIZATION
<b>IN</b>	STAINLESS STEEL

### COLOUR TEMP.

<b>27K</b>	2700K
<b>3K</b>	3000K
<b>4K</b>	4000K



ACCESSORIES

