

Outdoor spotlight for ground installation
 Material: anodized anticorrosive turned aluminium
 Diffuser: ultra-white transparent tempered glass
 External CC (constant current) 350 mA driver for series connection, compliant with EN 61347-2-13 Standard, to be ordered separately
 Light source: constant current LED module
 Supplied with 1,5 m cable
 Finish: anodization

On request versions (additional code):
MT7 7 m cable length

Dimensions	Ø 27 x L 81 mm
Light source	LED
Wattage	2 W
Power supply	350 mA
System output	126 lm
System efficiency	63 lm/W
Color Rendering Index – CRI	80
LED energy class	F
Electrical insulation class	Class III
IP rating	IP 65/67
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Conformity	CE UK CA

CODE OPTIONS

FINISH

ON BLACK ANODIZATION

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

OPTIC

standard 27°
 optional optics
11 11°
42 42°

DART SPOT Ø 27 LED 2W – 350MA

1612


ACCESSORIES

**DART SPOT
STRAP**



1601

**DART SPOT
SPIKE**



1600

**ACCESSORIES
CC 350 MA DRIVER – 3,6W**



1975

**ACCESSORIES
CC 350 MA DRIVER – 14W**



1976