



Outdoor spotlight for ground installation

Material: luminaire in anodized anticorodal turned aluminium /
Anti-glare shield in anodized anticorodal extruded aluminium

Diffuser: ultra-white transparent tempered glass

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: LED module

Supplied with 1,5 m cable

Finish: anodization

On request versions (additional code):

MT7 7 m cable length

Dimensions	Ø 30 x L 95 mm
Light source	LED
Wattage	2 W
Power supply	24 Vdc
System output	126 lm
System efficiency	63 lm/W
Color Rendering Index – CRI	80
LED energy class	F
Electrical insulation class	Class III
IP rating	IP 65/67
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	0.19 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

OS NATURAL ANODIZATION
ON BLACK ANODIZATION

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

OPTIC

standard 27°

optional optics

11 11°
42 42°

DART SPOT Ø 30 LED 2W – 24V

1615

ACCESSORIES

ACCESSORIES
24V DRIVER – 24W



1924

ACCESSORIES
24V DRIVER – 60W



1925

DART SPOT
STRAP



1601

DART SPOT
SPIKE



1600

ACCESSORIES
PWM DRIVER



1953