



Outdoor spotlight for ground installation  
 Material: anodized anticorodal turned aluminium  
 Diffuser: ultra-white transparent tempered glass  
 Built-in driver  
 Light source: LED unit  
 Supplied with 1,5 m cable  
 Finish: anodization

On request versions (additional code):  
**MT7** 7 m cable length

Dimensions	<b>Ø 46 x L 122 mm</b>
Light source	<b>LED</b>
Wattage	<b>4 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>470 lm</b>
System output	<b>355 lm</b>
System efficiency	<b>89 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>E (3000K), E (4000K), F (2700K)</b>
LED lifetime	<b>L80 B10 86.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class I</b>
IP rating	<b>IP 65/67</b>
Impact resistance rating	<b>IK 08 (5 Joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>0.54 kg</b>
Conformity	<b>CE UK CA</b>

**CODE OPTIONS**

**FINISH**

**ON** BLACK ANODIZATION

**COLOUR TEMP.**

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

**OPTIC**

**standard** 30°  
 optional optics  
**10** 10°  
**54** 54°



ACCESSORIES

